

FERRI ANGOLARI AD ALI UGUALI


Qualità:
- S275JR

dimensioni larghezza x spessore (mm)	peso (kg/m)
15 x 3	0,64
20 x 3	0,88
20 x 4	1,14
25 x 3	1,11
25 x 4	1,45
25 x 5	1,77
30 x 3	1,36
30 x 4	1,78
30 x 5	2,18
30 x 6	2,56
35 x 4	2,09

dimensioni larghezza x spessore (mm)	peso (kg/m)
35 x 5	2,57
35 x 6	3,04
40 x 4	2,42
40 x 5	2,97
40 x 6	3,52
45 x 4	2,74
45 x 5	3,38
45 x 6	4,00
50 x 4	3,06
50 x 5	3,77
50 x 6	4,47

dimensioni larghezza x spessore (mm)	peso (kg/m)
50 x 8	5,82
60 x 5	4,56
60 x 6	5,42
60 x 8	7,09
60 x 10	8,69
70 x 7	7,38
80 x 6	7,34
80 x 8	9,66
80 x 10	11,90
90 x 9	12,20
100 x 6	9,29

dimensioni larghezza x spessore (mm)	peso (kg/m)
100 x 8	12,20
100 x 10	15,10
100 x 12	17,80
120 x 10	18,20
120 x 12	21,60
150 x 15	33,80
200 x 15	48,57
200 x 20	59,90



PROFILATI A T

Qualità:
- S275JR

dimensioni profilo base (mm)	altezza (mm)	spessore (mm)	peso (kg/m)
20	20	4,0	1,13
25	25	4,5	1,61
30	30	5,0	2,16
35	35	5,5	2,78
40	40	6,0	3,49

dimensioni profilo base (mm)	altezza (mm)	spessore (mm)	peso (kg/m)
45	45	6,5	4,26
50	50	7	5,11
60	60	8	7,03
80	80	9	10,70
100	100	11	16,40

