


PROFILATI A U SERIE NORMALE

Qualità:
- S275JR

h (mm)	b (mm)	s (mm)	e (mm)	r (mm)	peso (kg/m)
30	33	5	7	7	4,27
40	35	5	7	7	4,87
50	38	5	7	7	5,59
65	42	5,5	7,5	7,5	7,09
80	45	6	8	8	8,65
100	50	6	8,5	8,5	10,6
120	55	7	9	9	13,3
140	60	7	10	10	16,0
160	65	7,5	10,5	10,5	18,9
180	70	8	11	11	22,0

h (mm)	b (mm)	s (mm)	e (mm)	r (mm)	peso (kg/m)
200	75	8,5	11,5	11,5	25,3
220	80	9	12,5	12,5	29,4
240	85	9,5	13	13	33,2
260	90	10	14	14	37,9
280	95	10	15	15	41,9
300	100	10	16	16	46,1
320	100	14	17,5	17,5	59,5
350	100	14	16	16	60,6
380	102	13,5	16	16	63,1
400	110	14	16	16	71,8



PROFILATI A U SERIE SPECIALE

Qualità:
- S275JR

h (mm)	b (mm)	s (mm)	(kg/m)
25	12	4	1,30
30	15	5	1,98
35	17	5,5	2,52
40	20	6	3,23
50	25	6	4,15
60	30	6,5	5,45